



TECHNICAL DATASHEET

REFERENCE : E5800-722

Old référence :

Green & Gold Polycarbonate Visor stitched on aluminized fabric

Description :

Screen in green polycarbonate covered with a gold layer. 500 x 250 x 1 mm (E9211-112). Sewed with para-aramid threads on an aluminized fabric to increase the surface of protection. The support and the gold layer filter the infrared and the UV – the gold layer on the extern side is covered of a varnish which brings a better mechanical resistance to scratch. Resistance to radiant heat up to 135°C continually. Adjustable visor on helmet by the universal liftable mount system ref 9100 and the headgear E9020 equip the 1000-722 outfit – the "AUGENSEIT" mark means side towards the eye



Dimensions : 500 x 250 x 1 mm

Sizes available Unique

Recommandation

Impact of average intensity (Index B), anti UV (index 4), radiant heat (infrared index 3 or 5), projections of molten metal and solid hot pieces (index 9), optical class (index 1)

The materials of this article do not contain any substance that can harm the health of the user

This PPE is in conformity with the requirements of the Directive 89/686/CEE. has been the subject of the(UHL) 0196-0237-MPA-96

The CE marking on these items means the respect for the essentials requirements of European Directive on PPE based on the standard



4-5 1 B 9

EN 166

- A** Limited flame spread
- B** Convective Heat (1 à 3)
- C** Radiant Heat (1 à 4)
- D** Projection of molten aluminium (1 à 3)
- E** Projection of molten iron (1 à 3)
- F** Contact Heat (1 à 3)

Use only within the risks covered above

Maintenance :



A dirty clothe may cause a reduced protection/ clean with a wet sponge, no alcohol or detergent. Flat or vertical storage.

Storage : Protected from the light and in a dry place, free of moisture, oils, greases...

Recommandation : Wear additional PPE, in case of high radiant heat, use a mineral glass visor Triplex (E5800-100P)

Coat/Apron		Sizes	B et C
	Lenght		
	120 cm	A	S – T2 92-96 cm
	130 cm	164-170 cm	M – T3 96-104 cm
	140 cm	170-182 cm	L – T4 104-112 cm
	150 cm	182-188 cm	XL – T5 112-120 cm
	160 cm	188-194 cm	XXL – T6 120-128 cm
	194-200 cm		

For coveralls, take the greatest size between **B** or **C**. The measures must be taken on the person wearing his work clothes, because this equipment is worn over. In doubt between two sizes choose the larger one.