

TECHNICAL DATASHEET

HTR Split leather gloves - 5 Finger

HTR treated split leather glove with HTR treated split leather cuff, arterial protection, Also available with

REFERENCE: E4554-404

Old référence :

Description:



Recommandation

Dimensions: 40cm

Sizes availaible one size 10/11

contact heat up to 250°C, protects from molten letal splashes. Perfect for welding or oxycutting.


The materials of this article do not contain any substance that can harm the health of the user

This PPE is in conformity with the requirements of the UE 2016/425 has been the subject of the 03306326 CENTEXBEL

wool blanket liner for greater flexibility and dexterity.

Total length: 40cm - Size: 10 - Ref E4554-404 wool swansdown liner, All threads in Kevlar®

The CE marking on these items means the respect for the essentials requirements of European Directive on PPE based on the standard EN 420



4131X4 **ABCDEF**

EN 407

3122

ABCD EN 388 A Burning behavior

B Contact Heat

C Convective heat D Radiant heat

E Small splashes of molten metal

F Large splashes of molten metal

« x » non tested

A Abrasion

B Blade cutting

C Tear resistance

D Perforation

Use only within the risks covered above

Maintenance: XXXXXX

The washing of gloves or mittens can alter the performance, so it's not recommended to wash them. Grease or oil on a glove can ignite, a wet glove transmits faster heat.washing is not advised.

Storage: Protected from the light and in a dry place, free of moisture, oils, greases...

Recommandation: must be worn with adapted PPE such as fire retardant clothes and helmet